

SPETEC® PLUG

WATER-SWELLABLE PLUG TO SEAL OFF FORMWORK SPACERS



DESCRIPTION

Plug made of a white semi hard plastic with a tip of swellable polymers. The ribbed structure of the plug provides a first barrier against water ingress while the swelling of the tip when in contact with water will provide as secondary barrier.

ADVANTAGES

- Easy installation.
- No special tools required
- No after-treatment required
- Good overall chemical resistance

FIELDS OF APPLICATION

- All formwork spacers made out of plastic, PVC or metal with an internal diameter of 22, 24, 26, 32, 34 mm.

APPLICATION

Note : the following is a typical application description. In case of other jobsite parameters, please contact our technical department.

REQUIRED TOOLS

Hammer

PREPARATION OF THE SUBSTRATE

Clean the surfaces of the spacer from dust, oil patches and other debris by brushing or compressed air.

PREPARATION OF THE PRODUCT

SPETEC® PLUG is ready for use.

APPLICATION

Simply position the plug on the opening of the spacer with the blue head facing towards the opening. Gently hammer the plug into the hole. No additional finishing is required.

FINISHING

No additional finishing is required.

APPLICATION CONDITIONS

SPETEC® PLUG can be applied under all weather conditions.

ADVICE / FOCAL POINTS

It's recommended to contact the SPETEC® representative in case of special applications.

TECHNICAL DATA

APPEARANCE - COMPOSITION

Round, white semi-hard plastic with a blue tip of swellable polymer.

CONSUMPTION

1 plug per end of a spacer.

TECHNICAL DATA

Property	Value
Diameter	22, 24, 26, 32, 34 mm
Pressure Resistance	6 bar
Expansion of the tip	up to 800% (after 5 days)

CHEMICAL RESISTANCE

- Good overall chemical resistance.

REFERENCE DOCUMENTS



PACKAGING

Diameter in mm	pieces/bag	pieces/box
22	100	1000
24	100	500
26	100	500
32	100	500
34	100	500

STORAGE AND SHELF LIFE

SPETEC® PLUG should be stored under cover, clear of the ground. Protect the materials from all sources of moisture and frost. Storage temperature must be between +5°C and +30°C. Shelf life is unlimited in correct storage conditions.

SAFETY PRECAUTIONS

Always use personal protective equipment in compliance with local regulations. Read the relevant Material Safety Data Sheet before use. Material Safety Data Sheets are available on www.spetec.com. When in doubt contact SPETEC® Technical Service.

The above information is provided in good faith, but without any guarantees. The application, use and processing of the products are beyond our control and are, as such, the sole responsibility of the user/processor. In the event that Resiplast N.V. is still held liable for damages, then the claim will still be limited to the value of the goods delivered. We always aim to deliver consistently high quality goods. All values on this technical sheet are average values that result from tests carried out under laboratory conditions (20°C and 50% RH). Values that are measured on the construction site may show a slight deviation since the environmental conditions, the application, and the way of processing our products are beyond our control. Do not add any products other than those indicated on the technical documentation. This version replaces all previous versions. Version 2.0 Date: 22 May 2020 10:44 am

RESIPLAST

RESIPLAST® - A brand of KORAMIC Construction Chemicals.
 Gulkenrodestraat 3 - B-2160 Wommelgem - België
info@resiplast.be - www.resiplast.be - Tel. +32 3 320 02 11 - Fax. +32 3 322 63 80